PRODUCT SPECIFICATION

DATE	REV	ECN	DESCRIPTION
1/31/2006	В	11154	UPDATED DESCRIPTION


Parent Number: F16072-

Description: 16 26/30 TC AWM 1569 or 1007 TR-64 or

AWM I A/B OD 0.094"

DIAMETER: 0.094

 $TOLERANCE \pm : 0.002$



MIN AVG WALL: 0.015

MINIMUM WALL: 0.013

Stranding: 26/30 TC LHL

Style: UL: AWM 1569 OR 1007 CSA: TR-64 or AWM I A/B

Insulation: PVC

Print Legend: 16 AWG (1.31mm2) E57498 (PLANT ID CODE) (AWM LOGO) AWM 1569 105C OR 1007 80C 300V VW-1 -- 156205 CSA TR-64 90C FT1 OR AWM I A/B 105C 300V FT1

Voltage: 300V

Temperature: 1569=105C, 1007=80C, TR64=90C

Notes:

This product complies with European Directive 2011/65/EU (RoHS 2)

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer	Ap	pro	val	! :
	_	_		

Customer Part Nbr(s):				
Approved By:	Date:			
Title:	Company Name:			

COLEMAN CABLE, INC

1530 Shields Drive Waukegan, IL 60085

Phone: 1-800-323-9355

www.colemancable.com

