PRODUCT SPECIFICATION


DATEREVECNDESCRIPTION2/3/2010A21007SPECIFICATION UPDATED

Parent Number: F10137-

Description: 10 105/30 TC AWM 1569 or 1581 AWM I A/B

DIAMETER: 0.145

TOLERANCE ± : 0.003



Stranding: 105/30 TC LHL

Style: UL: AWM 1569 or 1581 CSA: AWM I A/B

MIN AVG WALL: 0.015
MINIMUM WALL: 0.013

Insulation: PVC

Print Legend: 10 AWG (5.261mm2) E57498 (PLANT ID CODE) (AWM LOGO) AWM 1569 105C OR 1581 80C 300V VW-1 --- 156205 AWM I A/B 105C 300V FT1

Voltage: 300V

Temperature: <u>1569=105C</u>, <u>1581=80C</u>

Notes: 1. Maximum DC Resistance at 20C = 1.11 Ohms/1,000ft per UL 1581.

This product complies with European Directive 2011/65/EU (RoHS 2)

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:		
Customer Part Nbr(s):		
Approved By:	Date:	
Title:	Company Name:	

Southwire

Copperfield[®]

1115 W. North Street Bremen, IN 46506 Phone: 1-574-546-5115