

AUTOMOTIVE PRIMARY WIRE

AUTOMOTIVE Revised Nov.2009

General Purpose Thermoplastic:

Polyvinyl chloride (PVC) insulated wire manufactured to SAE J1128 standards to meet the following specifications:

FORD: M1L 56A
CHRYSLER: MS-3450

| GPT Bare Copper 80°C 60 Volts | | | | |
|--------------------------------------|----------------|------------------|-----------------------|------------------|
| Product | #CU/MFT | Stranding | Wall Thickness | Min Order |
| GPT-20-7-B | 3.46 | 7/0126 | .023 | 55M |
| GPT-18-16-B | 4.94 | 16/0098 | .023 | 45M |
| GPT-18-61-B | 4.90 | 61/36 | .023 | 50M |
| GPT-16-19-B | 7.40 | 19/0113 | .023 | 30M |
| GPT-16-37-B | 7.15 | 37/32 | .023 | 40M |
| GPT-14-19-B | 11.90 | 19/0142 | .023 | 22M |
| GPT-12-19-B | 18.35 | 19/0117 | .026 | 23M |
| GPT-10-19-B | 29.40 | 19/0224 | .031 | 28M |
| GPT-8-19-B | 48.00 | 19/0282 | .037 | 25M |
| GPT-6-49-B | 80.75 | 49/0232 | .045 | 50M |
| GPT-6-37-B | 82.00 | 37/0266 | .045 | 20M |
| GPT-4-61-B | 122.00 | 61/0249 | .045 | 20M |
| GPT-4-133-B | 122.00 | 133/0170 | .045 | 20M |

DELPHI PACKARD: ESM-3012

| GPT Bare Copper 80°C 60 Volts | | | | |
|--------------------------------------|----------------|------------------|-----------------------|------------------|
| Product | #CU/MFT | Stranding | Wall Thickness | Min Order |
| GPT-0.5-MM | 3.46 | 7/0126 | .023 | 55M |
| GPT-0.8-MM | 4.94 | 16/0098 | .023 | 45M |
| GPT-1.0-MM | 7.40 | 19/0113 | .023 | 30M |
| GPT-2.0-MM | 11.90 | 19/0242 | .023 | 22M |
| GPT-3.0-MM | 18.35 | 19/0177 | .026 | 23M |
| GPT-5.0-MM | 29.40 | 19/0224 | .031 | 28M |
| GPT-8.0-MM | 48.00 | 19/0282 | .037 | 25M |

Minimum order requirement reflects quantity per color, per release. Different color quantities may be combined to determine pricing with solid colors treated separately from striped colors.

800-776-9223 (Ohio) 800-684-7823 (Texas)