

Lutze Electronic PLTC PVC, Unshielded

Flexible Electronic Cable with UL/CSA/CE/PLTC Approvals



Application

- Industrial grade PLTC electronic cable for machine tools, process instrumentation and controls, computer peripherals, HVAC technology, assembly and production lines, low voltage interconnect and other industrial applications including **installation in cable trays**

Characteristics

- Flexible for easy installation
- Easy strip design
- Color coded conductors
- Specially formulated jacket for oil resistance
- Premium durability
- Extended temperature range
- RoHS compliant
- **UL listed and NFPA 79 compliant**

Technical Data

Voltage	300V
Temperature	-25°C - +105°C
Bending radius	4 x cable OD
Conductor marking	See tables
Approvals	UL Type PLTC CMG AWM Style 2464 VW-1, CSA CMG/FT4 AWM II A/B CE Oil Res II Meets NEC 725, 760, 800 Class I Div. 2 (PLTC use only) RoHS

Construction

- Flexible stranded tinned copper conductors
- PVC insulation
- Oil resistant gray premium PVC jacket

Part No.	Description No. of conductors	OD - Ø ca. mm	OD - Ø inches	Weight Lbs/Mft	Copper Lbs/Mft
AWG 22 (19/34)					
A3032202	2	4.4	0.172	20	4
A3032203	3	4.6	0.180	24	7
A3032204	4	4.9	0.193	28	9
A3032206	6	5.6	0.222	38	14
A3032208	8	6.0	0.238	45	19
A3032210	10	7.2	0.282	55	24
A3032215	15	7.9	0.310	75	35
A3032220	20	8.7	0.341	93	47
A3032225	25	10.4	0.408	124	59
AWG 20 (19/32)					
A3032002	2	4.9	0.195	27	7
A3032003	3	5.2	0.204	35	11
A3032004	4	5.6	0.220	41	15
A3032006	6	6.5	0.254	58	22
A3032008	8	7.2	0.282	76	30
A3032010	10	8.2	0.323	94	37
A3032015	15	11.3	0.446	136	56
A3032020	20	12.7	0.500	182	75
A3032025	25	14.0	0.551	222	94

Color Code Table AWG 22

1-	Black	1-	Black
2-	Brown	2-	Red
3-	Red	3-	White
4-	Orange	4-	Green
5-	Yellow	5-	Orange
6-	Green	6-	Blue
7-	Blue	7-	Brown
8-	Purple	8-	Yellow
9-	Gray	9-	Purple
10-	White	10-	Gray
11-	White	11-	Pink
12-	White	12-	Tan
13-	White	13-	Red
14-	White	14-	Red
15-	White	15-	Red
16-	White	16-	White
17-	White	17-	White
18-	White	18-	White
19-	White	19-	White
20-	White	20-	White
21-	White	21-	White
22-	White	22-	White
23-	White	23-	White
24-	White	24-	White
25-	White	25-	White
			Red

04/15/2010 Subject to technical modification
USA: Lutze Inc.

13330 South Ridge Drive
Charlotte, NC 28273, USA
Phone: 704-504 0222 Fax: 704-504 0223
www.lutze.com info@lutze.com

1-800-447-2371

LUTZE Systematic Technology

www.lutze.com