



SAE J1128 TWP
Automotive Primary Wire
85°C

Features

Conductors available in tinned or copper
Insulation: 85°C PVC
RoHS and REACH Compliant

Product Design Options

Custom strand constructions
Custom diameter to meet design criteria
Various colors for base and stripe combinations
Packaging options: reels or drums

Compliances

Ford ESB-M1L120-A
Ford WSS-M1L120-A3
Chrysler MS-7889

Applications

Cables used for automotive electrical

AWG size	Number of Strands	Strand Size (ga)	Nom Cond OD (in)	Nom OD (in)	Min Avg Wall (in)	Approx. Net Weight (lbs/mft)	Approx. Cu (lbs/mft)
22	7	30	0.030	0.062	0.013	4	30
20	7	28	0.038	0.070	0.013	5	19
18	19	30	0.048	0.081	0.012	7	5
16	19	29	0.056	0.069	0.013	10	5
14	19	27	0.069	0.103	0.013	15	3
12	19	25	0.088	0.126	0.015	23	3
10	19	23	0.108	0.155	0.019	36	2
8	19	21	0.137	0.184	0.016	56	2

Customer Service Group

1 Prestolite Drive Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: www.prestolitewire.com