



Southwire®

SPECIFICATION SHEET

PRODUCT DESCRIPTION: 14-41 2/C CU SJT 105* 300V Paper

STOCK NUMBER: 56-46-93-01

JACKET:

NOMINAL OUTSIDE DIAMETER:	.340"	in.
NOMINAL WALL THICKNESS:	.030"	in.
COMPOUND:	Polyvinyl Chloride	

CONDUCTOR:

NUMBER OF CONDUCTORS:	2	
NOMINAL OUTSIDE DIAMETER:	.136"	in.
NOMINAL WALL THICKNESS:	.030"	in.
INSULATION COMPOUND:	Polyvinyl Chloride	
COPPER:	14 AWG 41X.010" SBC	

TEMPERATURE:

105°C - MAX
-20°C - MIN

FILLERS:

Paper filler

PRINT:

INK

(UL) VW-1 E46194 (M) SJT 2/C 14 AWG (2.08mm²) 105°C 300V (CSA) FT1,FT2 LL90458 (M)

PRODUCT MANUFACTURED IN ACCORDANCE TO:

UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194

CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL90458

SOUTHWIRE COMPANY

3800 Industrial Parkway
MINERAL WELLS, TEXAS 76067
TEL (940) 328-1047
FAX (940) 328-1013