

CABLETECH GLOBAL

SPECIFICATION SHEET

PRODUCT CODE: 702631Y

PRODUCT DESCRIPTION: SJTOW 14/2 105* DRY 60* C PAPER

JACKET:

NOMINAL OUTSIDE DIAMETER: .340" +/- .005" in.
NOMINAL WALL THICKNESS: .030" in.
COMPOUND: Polyvinyl Chloride

CONDUCTOR:

NUMBER OF CONDUCTORS: 2
NOMINAL OUTSIDE DIAMETER): .136" in.
NOMINAL WALL THICKNESS): .030" in.
COPPER: 14 AWG 41X010 SBC

TEMPERATURE: 105*

FILLERS: PAPER

PRINT: **INDENT**

PRINT DESCRIPTION: UL VW-1 E47523 M SJTOW 14/2 105* DRY 60°C WATER RESISTANT (CSA) FT1
FT2 LL26332 M

PRODUCT MANUFACTURED IN ACCORDANCE TO:

UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - CABLETECH GLOBAL FILE NO. E47523

CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - CABLETECH GLOBAL FILE NO. LL26332

CABLETECH GLOBAL

3800 Industrial Parkway
MINERAL WELLS, TEXAS 76067
TEL (940) 328-1047
FAX (940) 328-1013