

SJT

105°C PVC Cord. 300 Volts. Flexible Copper Conductors. PVC Insulation and Jacket. Rated for Hard-Usage Service Cords. Rated UL VW-1 and CSA FT1, FT2 Flame Resistant.



Image not to scale and for reference only. See Table 1 for Dimensions

CONSTRUCTION:

- Conductors:** Class K, Flexible stranded bare copper per ASTM B3 and B174
Insulation: Polyvinyl Chloride (PVC) - Refer to Table 1 for color code
Assembly: The insulated conductors are cabled together with fillers to form a round cable assembly. A tissue paper is applied over the cabled assembly to facilitate overall jacket removal.
Jacket: PVC - Refer to Table 1 for color

APPLICATIONS AND FEATURES:

Southwire Type SJT Flexible Cords are permitted for use as specified by Article 400 and related articles of the 2011 National Electric Code. Some typical applications for Type SJT Cord include, but are not limited to: Wiring for industrial machinery such as washing machines and other large appliances, heavy-duty portable tools, motors and temporary electrical power.

SPECIFICATIONS:

- ASTM B3, B174
- UL 62 - Type SJT
- CSA C22.2 No. 49 - Type SJT

SAMPLE PRINT LEGEND:

(UL) VW-1 E46194 SJT 3/C 18 AWG (0.824mm²) 105°C 300V (CSA) FT1, FT2 LL90458

TABLE 1 - WEIGHTS & MEASUREMENTS

Stock Code	Cond. Size (AWG)	No. of Cond.	No. of Strands	Insulation Thickness (mils)	Jacket Thickness (mils)	Jacket Color	Nominal OD (mils)	Nominal Weight (Lbs/Mft)	Color Code
592838xx	18	3	16	30	30	BLK	330	61	BLU/BRN/GRN-YLW

All dimensions are nominal and subject to normal manufacturing tolerances



Southwire Company, LLC | One Southwire Drive, Carrollton, GA 30119 | www.southwire.com

Copyright © 2016 Southwire Company, LLC. All Rights Reserved

