

NOMA CABLETECH SPECIFICATION SHEET

PRODUCT CODE: 700591

PRODUCT DESCRIPTION: STOW 14/3 41SBC POLY

JACKET:

NOMINAL OUTSIDE DIAMETER: 0.545" in.
NOMINAL WALL THICKNESS: .080" in.
COMPOUND: Polyvinyl Chloride

CONDUCTOR:

NUMBER OF CONDUCTORS: 3
NOMINAL OUTSIDE DIAMETER: .168" in.
NOMINAL WALL THICKNESS: .045" in.
INSULATION COMPOUND: Polyvinyl Chloride
COPPER: 14 AWG 41.X010" SBC

TEMPERATURE: 105C

FILLERS: Polypropylene

PRINT:

INDENT
(UL) VW-1 E47523 (M) STOW 14/3 600V 60°C WATER RESISTANT (CSA) FT1,FT2
LL26332 (M)

PRODUCT MANUFACTURED IN ACCORDANCE TO:

UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - NOMA CABLETECH FILE NO. E47523
CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - NOMA CABLETECH FILE NO. LL26332

NOMA CABLE TECH

3800 Industrial Parkway
MINERAL WELLS, TEXAS 76067
TEL (940) 328-1047
FAX (940) 328-1013