

1. CONDUCTOR:

- 1.1 Size and Material: 12 65/30 AWG nickel-plated copper wire.
- 1.2 O.D.: .091" nom.

2. INSULATION:

- 2.1 Spiral-wrapped PTFE skived tape.
- 2.2 Served fibreglass yarn.
- 2.3 Braided fibreglass yarn impregnated with a saturant to minimize fraying.
- 2.4 Marking on the insulation: as per UL and CSA Standards.
- 2.5 O.D.: .142" nom.
- 2.6 Color: tan.

3. PERFORMANCE:

- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 250°C




4. REFERENCES:

- 4.1 UL Subject 758 (AWM), Style 5256.
- 4.2 CSA Standard C22.2 No.210 (AWM), Class I Group A/B.

CUSTOMER APPROVAL

Sign: _____

Date: _____

Engineering Change Notice No.								 <p>This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.</p>	Done: <i>Pierre Garand</i> Date: December 7, 2012		 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourtd.com		
1233	1345	1920							Verified: <i>David</i> Date: December 7, 2012		Description: TG600 1265/30N-T		
									Size: A Scale: --- Page: 1 of 1				
UNCONTROLLED DOCUMENT A later revision of this specification may exist.									 A member of The Marmon Group of companies				