

# Silicone - Type 3239 10kV

High Voltage Appliance Wire

UL: 150°C, 10kV



IEWC Part Number	AWG	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight	
			in	mm	in	mm	lbs/1k ft	kg/km
<b>3239/24T07S10</b>	24	7/32	0.040	1.0	0.104	2.6	6	9
<b>3239/22T07S10</b>	22	7/30	0.040	1.0	0.109	2.8	7	10
<b>3239/20T10S10</b>	20	10/30	0.040	1.0	0.119	3.0	8	12
<b>3239/18T16S10</b>	18	16/30	0.040	1.0	0.125	3.2	11	16
<b>3239/16T26S10</b>	16	26/30	0.040	1.0	0.137	3.5	14	21
<b>3239/14T41S10</b>	14	41/30	0.040	1.0	0.152	3.9	21	31
<b>3239/12T65S10</b>	12	65/30	0.040	1.0	0.167	4.2	29	43
<b>3239/10T105S10</b>	10	105/30	0.040	1.0	0.190	4.8	42	62

## Notes

- Soft-annealed, tinned copper conductor
- Extruded silicone rubber insulation
- RoHS Compliant
- Standard insulation colors: white, black and red

## Applications

For use in electronic and appliance applications. Rated for continuous use up to 150°C.