

# Silicone - Type 3239 15kV (TV)

High Voltage Hook-up Wire

UL: 150°C, 15kV

CSA: 150°C, 15kV



IEWC Part Number	AWG	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight	
			in	mm	in	mm	lbs/1k ft	kg/km
<b>3239/24T07S15</b>	24	7	0.045	1.1	0.114	2.9	7	10
<b>3239/22T07S15</b>	22	7	0.045	1.1	0.119	3.0	8	12
<b>3239/20T10S15</b>	20	10	0.045	1.1	0.129	3.3	9	13
<b>3239/18T16S15</b>	18	16	0.045	1.1	0.135	3.4	12	18
<b>3239/16T26S15</b>	16	26	0.045	1.1	0.147	3.7	16	24
<b>3239/14T41S15</b>	14	41	0.045	1.1	0.162	4.1	22	33
<b>3239/12T65S15</b>	12	65	0.045	1.1	0.177	4.5	30	45
<b>3239/10T105S15</b>	10	105	0.045	1.1	0.200	5.1	44	65

### Notes

- Soft-annealed, tinned copper conductor
- Extruded silicone rubber insulation
- RoHS Compliant
- Standard insulation colors: white, black and red

### Applications

For use in electronic and appliance applications. Rated for continuous use up to 150°C.