

# Silicone - Type 3239 30kV (TV)

High Voltage Hook-up Wire

UL: 150°C, 30kV

CSA: 150°C, 30kV



IEWC Part Number	AWG	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight	
			in	mm	in	mm	lbs/1k ft	kg/km
<b>3239/24T07S30</b>	24	7	0.075	1.9	0.174	4.4	14	21
<b>3239/22T07S30</b>	22	7	0.075	1.9	0.179	4.5	15	22
<b>3239/20T10S30</b>	20	10	0.075	1.9	0.189	4.8	17	25
<b>3239/18T16S30</b>	18	16	0.075	1.9	0.195	5.0	20	30
<b>3239/16T26S30</b>	16	26	0.075	1.9	0.207	5.3	24	36
<b>3239/14T41S30</b>	14	41	0.075	1.9	0.222	5.6	31	46
<b>3239/12T65S30</b>	12	65	0.075	1.9	0.237	6.0	40	60
<b>3239/10T105S30</b>	10	105	0.075	1.9	0.260	6.6	55	82

## Notes

- Soft-annealed, tinned copper conductor
- Extruded silicone rubber insulation
- RoHS Compliant
- Standard insulation colors: white, black and red

## Applications

For use in electronic and appliance applications. Rated for continuous use up to 150°C.