

# Silicone - Type 3239 40kV

High Voltage Hook-up Wire

UL: 150°C, 40kV



IEWC Part Number	AWG	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight	
			in	mm	in	mm	lbs/1k ft	kg/km
<b>3239/24T07S40</b>	24	7	0.097	2.5	0.218	5.5	21	31
<b>3239/22T07S40</b>	22	7	0.097	2.5	0.223	5.7	22	33
<b>3239/20T10S40</b>	20	10	0.097	2.5	0.233	5.9	25	37
<b>3239/18T16S40</b>	18	16	0.097	2.5	0.239	6.1	28	42
<b>3239/16T26S40</b>	16	26	0.097	2.5	0.251	6.4	33	49
<b>3239/14T41S40</b>	14	41	0.097	2.5	0.266	6.8	40	60
<b>3239/12T65S40</b>	12	65	0.097	2.5	0.281	7.1	50	74
<b>3239/10T105S40</b>	10	105	0.097	2.5	0.304	7.7	66	98

### Notes

- Soft-annealed, tinned copper conductor
- Extruded silicone rubber insulation
- RoHS Compliant
- Standard insulation colors: white, black and red

### Applications

For use in electronic and appliance applications. Rated for continuous use up to 150°C.