

126-00000



Article Number: 126-00000

Cable Tie and Edge Clip, 50 lbs, 8" Long, EC13, Panel Thickness .04"-.12", PA66HS, Black, 500/bag



Download drawing



Download spec sheet

Base Data

Local Order Number 126-00000

Type T50SOSEC13E

Color Black (BK)

- Features and Benefits**
- Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.
 - Edge Clip provides low insertion force and high extraction force ideal for assembly environments.
 - Two piece assembly allows the mount to slide along the strap ensuring proper orientation.
 - Cable tie is outside serrated to reduce bundle chafing.

Product Description The cable tie and edge clip assembly is ideal for use where holes are not acceptable or where adhesives will fail due to temperature problems. Edge clips are widely used for fixing and bundling cables and wires within automotive, trucking, heavy equipment, solar panel, wind power, and white goods equipment manufacturing.

Fixation Method (FF) Edge Clips

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Outside Serrated

Short Description Cable Tie and Edge Clip, 50 lbs, 8" Long, EC13, Panel Thickness .04"-.12", PA66HS, Black, 500/bag

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 180 N

Length L (Imperial) 6.0 "

Length L (Metric) 160.0 mm

Length L2 (Imperial) 0.6 "

Length L2 (Metric) 15.0 mm

Width W (Imperial) 0.18 "

Width W (Metric) 4.6 mm

Width W2 (Imperial) 0.43 "

Width W2 (Metric) 11.0 mm

Height H (Imperial) 0.06 "

Height H (Metric) 1.35 mm

Height H2 (Imperial) 0.591 "

Bundle Diameter Min. (Imperial) 0.04 "

Bundle Diameter Min. (Metric) 1.0 mm

Bundle Diameter Max. (Imperial) 1.4 "

Bundle Diameter Max. (Metric) 35.0 mm
Panel Thickness Max. (Imperial) 0.12 "
Panel Thickness Min. (Imperial) 0.04 "
Thickness T (Imperial) 0.05 "
Thickness T (Metric) 1.35 mm

Logistics and Packaging

Quantity Per bag
Package Quantity (Metric) 500 Pieces
Carton Quantity 5000 Pieces
Weight (Metric) 1.95 kg

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut PA66HS
Flammability UL94 V2
Operating Temperature -40°F to +221°F (-40°C to +105°C)
ROHS compliant (Article 4 - 1) Yes