

156-00157

Article Number: 156-00157

Fir Tree with Tie, 8.0" Long, Mounting Hole Diameter .26"-.28", PA66HS, Black, 500/pkg



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 156-00157

**Type** T50RFT6

**Color** Black (BK)

- Features and Benefits**
- Staggered fir tree branch design provides low insertion forces and high extraction forces.
  - Initial fir tree serves as a locating feature for assistance in blind assembly applications.
  - Disc feature provides anti-rattle protection in high vibration applications.

**Product Description** HellermannTyton's fir tree mounts provide a secure grip in a mounting hole and protect against dirt and other impurities. The mount can slide along the strap of the cable tie for proper orientation. The fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie.

**Fixation Method (FF)** Fir Tree

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** Fir Tree with Tie, 8.0" Long, Mounting Hole Diameter .26"-.28", PA66HS, Black, 500/pkg

## Product Dimensions

**Minimum Tensile Strength (Imperial)** 50.0 lbs

**Minimum Tensile Strength (Metric)** 225 N

**Length L (Imperial)** 8.0 "

**Length L (Metric)** 202.0 mm

**Length L2 (Imperial)** 0.46 "

**Length L2 (Metric)** 11.6 mm

**Length L3 (imperial)** 0.53 "

**Length L3 (metric)** 13.8 mm

**Width W (Imperial)** 0.18 "

**Width W (Metric)** 4.6 mm

**Width W2 (Imperial)** 0.35 "

**Width W2 (Metric)** 9.0 mm

**Width W3 (Imperial)** 0.2 "

**Width W3 (Metric)** 5.0 mm

**Height H (Imperial)** 0.05 "

**Height H (Metric)** 1.2 mm

<b>Height H2 (Imperial)</b>	0.3 "
<b>Height H2 (Metric)</b>	7.5 mm
<b>Bundle Diameter Min. (Imperial)</b>	0.06 "
<b>Bundle Diameter Min. (Metric)</b>	5.0 mm
<b>Bundle Diameter Max. (Imperial)</b>	2.0 "
<b>Bundle Diameter Max. (Metric)</b>	44.5 mm
<b>Disc Diameter (Imperial)</b>	0.63 "
<b>Disc Diameter (Metric)</b>	16.0 mm
<b>Panel Thickness Max. (Imperial)</b>	0.12 "
<b>Panel Thickness Min. (Imperial)</b>	0.03 "
<b>Mounting Hole Diameter D (Imperial)</b>	0.26 - 0.28 "
<b>Mounting Hole Diameter D (Metric)</b>	6.5 - 7.0 mm
<b>Mounting Hole Diameter D Min. (Imperial)</b>	0.252 "
<b>Mounting Hole Diameter D Max. (Imperial)</b>	0.28 "
<b>Mounting Hole Diameter D Max. (Metric)</b>	7.0 mm
<b>Mounting Hole Diameter D Min. (Metric)</b>	6.5 mm
<b>Thickness T (Metric)</b>	1.2 mm

## Logistics and Packaging

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	500
<b>Carton Quantity</b>	3000

## Material and Specifications

<b>Material</b>	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS) Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HIRHS PA66HS
<b>Material Cable Tie</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Edge Clip</b>	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
<b>Flammability</b>	UL94 HB
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS compliant (Article 4 - 1)</b>	Yes