

Features and Benefits



Comprehensive diagnostics

- When test button is actuated, both the electronic components and mechanical trip mechanism are functionally tested

Ground fault indicator

- Flashing RED indicates device has lost capability to provide protection

No power at face if reverse wired

- Open circuit condition eliminates false assumption of protection at face



**Commercial Series
LED, GFCI**
15 and 20 Ampere
125 Volts
2-Pole, 3-Wire Grounding



Description	Color	Catalog Numbers	
Commercial LED.	Brown	GF15L	GF20L
	Ivory	GF15IL	GF20IL
	White	GF15WL	GF20WL
	Office White	GF15OWL	GF20OWL
	Almond	GF15ALL	GF20ALL
	Light Almond	GF15LAL	GF20LAL
	Gray	GF15GYL	GF20GYL
	Black	GF15BKL	GF20BKL
	Red	GF15RL	GF20RL
Hospital Grade LED.	Brown	GFR8200HL	GFR8300HL
	Ivory	GFR8200HIL	GFR8300HIL
	White	GFR8200HWL	GFR8300HWL
	Office White	GFR8200HOWL	GFR8300HOWL
	Almond	GFR8200HALL	GFR8300HALL
	Gray	GFR8200HGYL	GFR8300HGYL
	Black	GFR8200HBKL	GFR8300HBKL
Red	GFR8200HRL	GFR8300HRL	

Description	Color	Catalog Numbers
Combination Switch/ LED GFCI.	Brown	GFSP15
	Ivory	GFSP15I
	White	GFSP15W
	Almond	GFSP15AL
	Black	GFSP15BK

**Commercial Series
Combination
Switch/GFCI**
15 Ampere
125 Volts
2-Pole, 3-Wire Grounding

Note: GFCI type receptacles should not be used in critical care patient areas or for electrical life support equipment applications because of the possibility of power interruption. All GFCI receptacles listed above are furnished with the proper color nylon wallplate.