




PLT-XMR Reel-Fed Cable Ties

- Continuously molded cable ties (5,000 ties/reel) provide continuous feeding for high productivity and reduced downtime due to fewer reel changes
- All-nylon, one-piece locking ties with 18 lbs. minimum loop tensile strength in miniature cross section
- Available in a variety of colors and materials
- Reel-fed cable ties in Nylon 6.6 material (except black) are UL Listed for use in plenum or air handling spaces per NEC



| Part Number | Tie Style | Material | Color | Max. Bundle Dia. | | Length | | Width | | Min. Loop Tensile Str. | |
|---|-----------|-----------------------------|---------|------------------|----|--------|-----|-------|-----|------------------------|----|
| | | | | In. | mm | In. | mm | In. | mm | Lbs. | N |
| Reel-Fed Cable Ties for PAT1M System | | | | | | | | | | | |
| PLT1M-XMR | All-Nylon | Nylon 6.6 | Natural | .82 | 21 | 4.0 | 102 | .100 | 2.5 | 18 | 80 |
| PLT1M-XMR0 | All-Nylon | Weather Resistant Nylon 6.6 | Black | .82 | 21 | 4.0 | 102 | .100 | 2.5 | 18 | 80 |
| PLT1M-XMR00* | All-Nylon | Weather Resistant Nylon 6.6 | Black | .82 | 21 | 4.0 | 102 | .100 | 2.5 | 18 | 80 |
| PLT1M-XMR1 | All-Nylon | Nylon 6.6 | Brown | .82 | 21 | 4.0 | 102 | .100 | 2.5 | 18 | 80 |
| PLT1M-XMR2 | All-Nylon | Nylon 6.6 | Red | .82 | 21 | 4.0 | 102 | .100 | 2.5 | 18 | 80 |
| PLT1M-XMR3 | All-Nylon | Nylon 6.6 | Orange | .82 | 21 | 4.0 | 102 | .100 | 2.5 | 18 | 80 |
| PLT1M-XMR4Y | All-Nylon | Nylon 6.6 | Yellow | .82 | 21 | 4.0 | 102 | .100 | 2.5 | 18 | 80 |
| PLT1M-XMR5 | All-Nylon | Nylon 6.6 | Green | .82 | 21 | 4.0 | 102 | .100 | 2.5 | 18 | 80 |
| PLT1M-XMR6 | All-Nylon | Nylon 6.6 | Blue | .82 | 21 | 4.0 | 102 | .100 | 2.5 | 18 | 80 |
| PLT1M-XMR7 | All-Nylon | Nylon 6.6 | Purple | .82 | 21 | 4.0 | 102 | .100 | 2.5 | 18 | 80 |
| PLT1M-XMR8 | All-Nylon | Nylon 6.6 | Gray | .82 | 21 | 4.0 | 102 | .100 | 2.5 | 18 | 80 |
| PLT1M-XMR10 | All-Nylon | Nylon 6.6 | White | .82 | 21 | 4.0 | 102 | .100 | 2.5 | 18 | 80 |
| PLT1M-XMR30 | All-Nylon | Heat Stabilized Nylon 6.6 | Black | .82 | 21 | 4.0 | 102 | .100 | 2.5 | 18 | 80 |

Reel-Fed Cable Ties for PAT1.5M System

| | | | | | | | | | | | |
|----------------|-----------|-----------------------------|---------|------|----|-----|-----|------|-----|----|----|
| PLT1.5M-XMR | All-Nylon | Nylon 6.6 | Natural | 1.31 | 33 | 5.6 | 142 | .100 | 2.5 | 18 | 80 |
| PLT1.5M-XMR0 | All-Nylon | Weather Resistant Nylon 6.6 | Black | 1.31 | 33 | 5.6 | 142 | .100 | 2.5 | 18 | 80 |
| PLT1.5M-XMR00* | All-Nylon | Weather Resistant Nylon 6.6 | Black | 1.31 | 33 | 5.6 | 142 | .100 | 2.5 | 18 | 80 |
| PLT1.5M-XMR30 | All-Nylon | Heat Stabilized Nylon 6.6 | Black | 1.31 | 33 | 5.6 | 142 | .100 | 2.5 | 18 | 80 |

*Military grade weather resistant material.

Note: PLT_XMR cable ties (natural, 00, and colors) are Class 2 Mil. Spec. per SAE-AS23190A and SAE-AS33671.

A. System Overview

B1. Cable Ties

B2. Cable Accessories

B3. Stainless Steel Ties

C1. Wiring Duct

C2. Surface Raceway

C3. Abrasion Protection

C4. Cable Management

D1. Terminals

D2. Power Connectors

D3. Grounding Connectors

E1. Labeling Systems

E2. Labels

E3. Pre-Printed & Write-On Markers

E4. Permanent Identification

E5. Lockout/Tagout & Safety Solutions

F. Index