




Ring Terminal, Vinyl Insulated – Funnel Entry

Type PV-R

- Insulation support helps to prevent wire damage in bending applications
- Ring tongue design assures a secure connection in high vibration applications
- Brazed seam protects terminal barrel from splitting during the crimp process
- Internal barrel serrations assure good wire contact and maximum tensile strength
- UL Flammability UL 94V-0, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up to 600 V per UL 486A/B



Part Number	Wire Range	Color Code	Stock Thickness (In.)	Max. Ins. (In.)	Stud Size	Figure Dimensions (In.)			Recommended Installation Tool	Std. Pkg. Qty.**	Std. Ctn. Qty.			
						L	W	C						
PV22-2R-CY*	26 – 22 AWG	Yellow	0.02	0.110	#2	0.68	0.21	0.18	CT-600-A, CT-1525, CT-2500	100	1000			
PV22-4R-CY*			0.02	0.110	#4	0.68	0.21	0.18		100	1000			
PV22-6R-CY*			0.02	0.110	#6	0.68	0.21	0.18		100	1000			
PV22-8R-CY*			0.02	0.110	#8	0.78	0.26	0.26		100	1000			
PV22-10R-CY*			0.02	0.110	#10	0.78	0.32	0.24		100	1000			
PV18-4R-CY	22 – 18 AWG	Red	0.03	0.150	#4	0.84	0.25	0.22	CT-100A‡, CT-600-A‡, CT-1550‡, CT-1551‡, CT-2500‡	100	500			
PV18-6R-CY			0.03	0.150	#6	0.86	0.25	0.22		100	500			
PV18-8R-CY			0.03	0.150	#8	0.91	0.31	0.26		100	500			
PV18-10R-CY			0.03	0.150	#10	0.94	0.31	0.27		100	500			
PV18-14R-CY			0.03	0.150	1/4"	1.11	0.46	0.37		100	500			
PV18-56R-CY			0.03	0.150	5/16"	1.11	0.46	0.39		100	500			
PV18-38R-LY			0.03	0.150	3/8"	1.19	0.53	0.42		50	500			
PV18-12R-LY			0.03	0.150	1/2"	1.42	0.72	0.53		50	500			
PV14-4R-C			16 – 14 AWG	Blue	0.03	0.170	#4	0.84		0.25	0.19	CT-100A‡, CT-600-A‡, CT-1550‡, CT-1551‡, CT-2500‡	100	500
PV14-6RN-C					0.03	0.170	#6	0.84		0.25	0.19		100	500
PV14-6R-C	0.03	0.170			#6	0.92	0.31	0.25	100	500				
PV14-8R-C	0.03	0.170			#8	0.92	0.31	0.25	100	500				
PV14-10R-C	0.03	0.170			#10	0.92	0.31	0.25	100	500				
PV14-14R-C	0.03	0.170			1/4"	1.12	0.46	0.38	100	500				
PV14-56R-C	0.03	0.170			5/16"	1.12	0.46	0.38	100	500				
PV14-38R-L	0.03	0.170			3/8"	1.21	0.53	0.43	50	500				
PV14-12R-L	0.03	0.170			1/2"	1.42	0.72	0.53	50	500				
PV10-6R-L	12 – 10 AWG	Yellow			0.04	0.225	#6	1.05	0.31	0.31	CT-100A‡, CT-600-A‡, CT-1550‡, CT-1551‡, CT-2500‡		50	500
PV10-8R-L			0.04	0.225	#8	1.05	0.31	0.31	50	500				
PV10-10R-L			0.04	0.225	#10	1.05	0.31	0.31	50	500				
PV10-14R-L			0.04	0.225	1/4"	1.23	0.52	0.38	50	500				
PV10-56R-L			0.04	0.225	5/16"	1.23	0.52	0.38	50	500				
PV10-38R-L			0.04	0.225	3/8"	1.31	0.58	0.41	50	500				
PV10-12R-Q			0.04	0.225	1/2"	1.46	0.72	0.53	25	250				

*Wire sizes #26 – 22 AWG, are not UL Listed or CSA Certified.

**Bulk and/or convenience packaging may be available, contact Panduit® Customer Service for additional information.

‡UL and CSA approved tooling/product combinations. For crimping tool information see www.panduit.com/tools.

B1.
Cable
Ties

B2.
Cable
Accessories

B3.
Stainless
Steel Cable
Ties &
Accessories

C1.
Wiring
Duct

C2.
Abrasion
Protection

C3.
Cable
Management

D1.
Terminals

D2.
Power
Connectors

D3.
Grounding
Connectors

E1.
Labeling
Systems

E2.
Labels

E3.
Pre-Printed
&
Write-On
Markers

E4.
Permanent
Identification

E5.
Industrial
Safety
Solutions

F.
Keystone
Cabling
Systems


G.
Part
Number
Index



Ring Terminal, Large Wire, Vinyl Insulated

Type PV-R

- Ring tongue design assures a secure connection in high vibration applications
- Insulation support helps to prevent wire damage in bending applications
- Brazed seam protects terminal barrel from splitting during the crimp process
- Internal barrel serrations assure good wire contact and maximum tensile strength
- UL Flammability UL 94V-0, maximum insulation temperature 221°F (105°C)
- UL rated up to 600 V per UL 486A/B



Part Number	Wire Range	Color Code	Stock Thickness (In.)	Max. Ins. (In.)	Stud Size	Figure Dimensions (In.)			Recommended Installation Tool	Std. Pkg. Qty.**	Std. Ctn. Qty.
						L	W	C			
PV8-8R-QY	8 AWG	Red	0.04	0.280	#8	1.51	0.42	0.43	CT-720, CD-720PV8-2‡, CT-2600, CD-2600-PV8‡	25	250
PV8-8RN-Q			0.04	0.280	#8	1.48	0.36	0.43		25	250
PV8-10R-QY			0.04	0.280	#10	1.53	0.47	0.43		25	250
PV8-14R-QY			0.04	0.280	1/4"	1.53	0.47	0.43		25	250
PV8-56R-QY			0.04	0.280	5/16"	1.64	0.59	0.49		25	250
PV8-38R-QY			0.04	0.280	3/8"	1.64	0.59	0.51		25	250
PV8-12R-XY			0.04	0.280	1/2"	1.74	0.82	0.51		10	100
PV6-8R-E	6 AWG	Blue	0.05	0.340	#8	1.61	0.47	0.43	CT-720, CD-720PV8-2‡, CT-2600, CD-2600-PV6‡	20	200
PV6-10R-X			0.05	0.340	#10	1.62	0.47	0.43		10	100
PV6-14R-X			0.05	0.340	1/4"	1.65	0.47	0.48		10	100
PV6-56R-X			0.05	0.340	5/16"	1.74	0.62	0.53		10	100
PV6-38R-X			0.05	0.340	3/8"	1.74	0.62	0.51		10	100
PV6-12R-X			0.05	0.340	1/2"	1.84	0.82	0.51		10	100
PV4-10R-E			4 AWG	Yellow	0.05	0.450	#10	1.88		0.55	0.50
PV4-14R-E	0.05	0.450			1/4"	1.88	0.55	0.50	20	200	
PV4-56R-E	0.05	0.450			5/16"	1.95	0.68	0.50	20	200	
PV4-38R-E	0.05	0.450			3/8"	1.95	0.68	0.50	20	200	
PV4-12R-E	0.05	0.450			1/2"	2.04	0.86	0.50	20	200	
PV2-10R-XY	2 AWG	Red	0.06	0.560	#10	1.96	0.68	0.58	CT-720, CD-720PV8-2‡, CT-2600, CD-2600-PV2‡	10	100
PV2-14R-XY			0.06	0.560	1/4"	1.96	0.68	0.58		10	100
PV2-56R-XY			0.06	0.560	5/16"	1.96	0.68	0.58		10	100
PV2-38R-XY			0.06	0.560	3/8"	1.96	0.68	0.58		10	100
PV2-12R-XY			0.06	0.560	1/2"	2.05	0.86	0.58		10	100

**Bulk packaging may be available, contact Panduit® Customer Service for additional information.

‡UL approved tooling/product combinations. For crimping tool information see www.panduit.com/tools.